



Soluble Cutting Oil SC-10™

Fully formulated water soluble cutting oil designed to reduce surface temperatures and extend tool life in a wide range of metalworking operations – Contains biocide to combat organism formation in machine reservoirs and sumps

Key Features & Benefits

- Extends tool life over conventional soluble oils
- Contains industry level biocide to reduce rancidity problems
- Provides smoother finishes
- Enhances cutting ability
- Protects work, tools and equipment from rust and corrosion
- Excellent cooling properties
- Forms a stable emulsion
- Provides process visibility (becomes milky white in appearance once emulsified with water)
- Can be used in a wide range of machining operations
- Contains multiple metalworking technologies, including ionic bonding agents and metal film strength reducers
- Contains **Muscle Metal Treatment MT-10®** technology for lubricity enhancement and friction-reducing properties

Typical Applications & Emulsion Ratios

- Light machining of soft to medium hardness steel
Typical emulsion ~ 20:1
- Grinding operations requiring excellent cooling & a lower ratio
Typical emulsion ~ 40:1

Directions for Use

Reduce **SC-10™** with water to the desired emulsion ratio depending on the operation.

Technical Data

Appearance	Dark amber liquid
Odor	Strong
pH	9.0 D-1287
Initial boiling point	257°F (125°C) D-1120
Flash point	305.6°F (152°C) D-93
Specific gravity @ 60°F.....	0.9383 D-1298
Lbs per gal (U.S).....	~ 7.59
Viscosity @ 40°C	40.09 cSt D-445
Viscosity @ 100°C	6.39 cSt D-445
Solubility	Dispersible in water

The above properties are typical values and do not constitute a product specification.

Container Availability

Item SC-10-128.....	1 U.S. gallon (3.8 L)
Item SC-10-5G.....	5 U.S. gallon (18.9 L)
Item SC-10-55G.....	55 U.S. gallon (208 L)

© 1986-2015 Muscle Products Corp. R.02